

Recommended Tooling Specifications

<u>Tool</u>	<u>Application</u>	<u>Diameter</u>	<u>Teeth</u>	<u>Hook</u>	<u>Kerf</u>	<u>Arbor</u>
Table Saw (over 3HP)	Ripping Lamboo	10"	24 ATB	20°	.126"	5/8"
		12"	30 TCG	12°	.118"	5/8"
	Crosscutting Lamboo	10"	80 ATB	10°	.116"	5/8"
		12"	96 ATB	10°	.116"	1"
	Combination Ripping/ Crosscutting Lamboo	10"	50 Comb.	10°	.126"	5/8"
		12"	60 Comb.	10°	.126"	1"
	Cross Ply Lamboo	10"	80 TCG	-3°	.126"	5/8"
		12"	80 HiATB	2°	.126"	5/8"
Sliding Compound Miter Saw / Radial Arm Saw	Crosscutting / General Cutting Lamboo	8"	48 ATB	-5°	.090"	5/8"
		10"	60 ATB	-5°	.090"	5/8"
		12"	72 ATB	-5°	.090"	1"
	Extra-fine Crosscutting Cross Ply Lamboo	10"	80 HiATB	2°	.091"	5/8"
		10"		-5°	.109"	5/8"
		12"		-5°	.109"	1"
Non-Sliding Compound Miter Saw	Crosscutting / General Cutting Lamboo	8"	64 ATB	10°	.116"	5/8"
		10"	80 ATB	10°	.116"	5/8"
		12"	96 ATB	10°	.116"	1"
	Extra-fine Crosscutting Cross Ply Lamboo	10"	80 HiATB	2°	.125"	5/8"
		12"	96 HiATB	2°	.125"	5/8"

****Carbide Tooling****

C4 Industrial Grade: Tungsten Level 88-92

